

Arch Linux

- [Arch User Repository](#)

Arch User Repository

Arch User Repository (AUR)

yay

makepkg debug

```
#####  
#####  
# GLOBAL PACKAGE OPTIONS  
# These are default values for the options=() settings  
#####  
#####  
#  
# Makepkg defaults: OPTIONS=(!strip docs libtool staticlibs emptydirs !zipman !purge !debug !lto)  
# A negated option will do the opposite of the comments below.  
#  
#-- strip: Strip symbols from binaries/libraries  
#-- docs: Save doc directories specified by DOC_DIRS  
#-- libtool: Leave libtool (.la) files in packages  
#-- staticlibs: Leave static library (.a) files in packages  
#-- emptydirs: Leave empty directories in packages  
#-- zipman: Compress manual (man and info) pages in MAN_DIRS with gzip  
#-- purge: Remove files specified by PURGE_TARGETS  
#-- debug: Add debugging flags as specified in DEBUG_* variables  
#-- lto: Add compile flags for building with link time optimization  
#  
OPTIONS=(strip docs !libtool !staticlibs emptydirs zipman purge !debug lto)
```

debug yay

```
sudo pacman -S --needed base-devel git
git clone https://aur.archlinux.org/yay.git
cd yay
makepkg -si
```

makepkg.conf



☐ MAKEFLAGS ☐ nproc ☐

```
MAKEFLAGS="-j$(nproc)"
```

☐ / ☐

```
yay -S pigz pbzip2 lbzip2 plzip
```

☐

```
COMPRESSGZ=(pigz -c -f -n)
COMPRESSBZ2=(pbzip2 -c -f)
COMPRESSXZ=(xz -c -z -)
COMPRESSZST=(zstd -c -T0 --ultra -20 -)
COMPRESSLRZ=(lrzip -q)
COMPRESSLZO=(lzop -q)
COMPRESSZ=(compress -c -f)
COMPRESSLZ4=(lz4 -q)
COMPRESSLZ=(plzip -c -f)
```